

Abloy EL580



Tootekirjeldus

Handle controlled locks can be set to function as fail locked or as fail unlocked. In the fail locked setting, the lock can be opened by handle when power is on and cannot be opened by handle when power is off. In the fail unlocked setting, the electrical function is reversed.

EL580 handle controlled lock case for solid doors

Applications:

- Interior and exterior doors of e.g. business premises, public buildings, hospitals and schools
- Fire rated doors
- Exit doors
- Not suitable for use with door automatics

Function:

- Handles on both sides of the door: outside handle is electrically controlled (e.g. by reader or push button), inside handle opens the lock always.

TOOTENIMETUS	SOODUS	HIND
Abloy EL580/50		520.53
		€

TOOTENIMETUS	SOODUS	HIND
<p> Abloy EL580L/50 1/4 (D±DμD· D·D°D;D³⁄₄Ñ€D¹⁄₂D³⁄₄D¹ D;D»D°D¹⁄₂D°D, D, D±DμD· D°D°D±DμD»Ñ•, 12-24D', D¹⁄₂D, D·D°D³⁄₄Dμ Ñ•D¹⁄₂DμÑ€D³⁄₄D;D³⁄₄Ñ,Ñ€DμD±D»DμD¹⁄₂D, Dμ, D°D°Ñ€D° 57/50) </p>		826.34€

