Abloy EL582



Tootekirjeldus

Handle controlled locks can be set to function as fail locked or as fail unlocked. In the fail locked setting, the lock can be opened by handle when power is on and cannot be opened by handle when power is off. In the fail unlocked setting, the electrical function is reversed.

Application:

- interior doors of e.g. business premises
- fire rated doors
- not suitable for use with door automatics

Function:

• both outside and inside handle are electrically controlled (e.g. by reader or push button).

Compatible products:

• Striker plate: LP717, LP722, LP732

TOOTENIMETUS	SOODUS	HIND
$D_{1}D_{2}D_{3}D_{4}D_{5}D_{4}D_{5}D_{5}D_{4}D_{5}D_{5}D_{5}D_{5}D_{5}D_{5}D_{5}D_{5$		520.54 €
$ \boxed{ D_i D^3 \!\!\!/ 4D \!\!\!> \!\!\!\! D\mu D^1 \!\!\!/_2 D^3 \!\!\!/ 4D_s D^2 D^1 \!\!\!/_2 \tilde{N} \!\!\!< \!\!\!\! D^1 D \cdot D^0 D^1 \!\!\!/_2 D^3 \!\!\!/ 4D^0 \text{ Abloy EL582/70 } D^1 \!\!\!/_2 D^1 \!\!\!/_2 D^1 D^2 D^2 D^2 D^2 D^2 D^2 D^2 D^2 D^2 D^2$		551.24 €

