

Abloy PE580



Tootekirjeldus

- For wooden or metal doors, with deadlocked latch bolt, fail locked/fail unlocked.
- Bolt position and handle operation.
- Outside handle controlled.

Features:

- Easily reversible trigger bolt and deadbolt, suitable for all hands of the door.
- Quick change fail locked to fail unlocked.
- Selectable 14mm or 20mm deadbolt throw (PE580: 14mm only).
- Automatic deadlocking of deadbolt only when the door shuts.
- Meeting EN179 and EN1125 for emergency and panic exit doors and EN1634-1 for fire resistance (inside handle can be operated at all times (EL580 and PE580 only)).
- Retrofits mechanical Scandinavian mortice locks.

Technical Specification:

- Operating voltage - 12V DC to 24V DC stabilised
- Current max Idle - 120mA, Max 350mA
- Temperature (°C) -20 to +60
- Backset(mm) - 50

Д-Д²Д°Д°ÑƒД°Ñ†Д,Ñ• сД³⁄₄Д»ДµД¹⁄₂Д³⁄₄Д,Д´Д¹⁄₂Ñ†Д¹ Д·Д°Д¹⁄₄Д³⁄₄Д° ABLOY
 PE580 (Д,Ñ€Д°Д²Д°Ñ• Ñ€ÑƒД°Д°, Д±ДµД· Д·Д°Д,Ñ€Д³⁄₄Ñ€Д¹⁄₂Д³⁄₄Д¹
 Д,Д»Д°Д¹⁄₂Д°Д,)

536.03 €

