

ASSA ABLOY DC700GFM



Tootekirjeldus

- Free-Motion® door closer with free-swing function starting from a door opening angle $\geq 0^\circ$, and height adjustable guide rail
- DIBt approval Z-6.5-2166 as a hold-open System with various smoke detector systems
- DIBt tested as a hold-open system with various smoke detector systems
- Certified in compliance with EN 1155/1154, size 3-6
- For single action doors up to 1400 mm wide
- Variants for door leaf mounting and frame mounting on hinge side
- Fulfills barrier-free building requirements (EA / CEN TR 15894)
- Suitable for fire and smoke protection doors (additional verification of suitability maybe required for the respective fire or smoke protection door)

Characteristics:

- Easy, initial door opening due to the rapidly decreasing opening force. When active, the free-swing function enables permanent opening of the door without the resistance of the door closer
- The door remains in free swing mode until the power supply is switched off
- Door leaf and frame mounting on hinge side, DIN left and DIN right doors
- Axis continuously height adjustable up to 14 mm
- Closing speed and latching speed adjustable via front facing regulating valves
- Variable adjustable closing force
- Opening angle up to 170°
- Thermodynamic valves for consistent performance

- Effective latching speed range adjustable

Compatible products:

- Sliding arms: [G795](#)
- Mounting plates: [A120](#), [A130 \(G795 jaoks\)](#)
- Stopper: [A153](#)

TOOTENIMETUS	SOODUS	HIND
?????? ???????? ASSA ABLOY FD740 EN 3-6, ?????? ?????????? ??? (????????????)		625.65 €