

ASSA 835C-50



Tootekirjeldus

The 835C-50 motor lock features an electronically controlled deadlatch (adjustable split spindle) as well as a mechanical hook bolt that provides increased holding force with an auto hook and auto retract function, it is certified according to EN179 which allows installation in escape routes.

The handle can be electronically activated from the outside, and is mechanically controlled from the inside; alternatively, the handle can be activated electronically from both the inside and outside to open the door.

Specifications:

- The lock can always be opened with a key/thumb turn
- Dead latched handle
- Certified according to SSF 3522-1093, class 3 and EN179, combined with ASSA ABLOY emergency exit hardware 179J.
- The re-entry function can be activated via I/O BOX 350 with a signal from an evacuation/fire alarm
- Multifunctional

TOOTENIMETUS	SOODUS	HIND
ASSA Connect 835C-50 D ¹ / ₄ D ³ / ₄ N̄,D ³ / ₄ N̄€D ¹ / ₂ N̄<D ¹ D·D°D ¹ / ₄ D ³ / ₄ D°		1293.20 €
ASSA Connect 835C-50 D ¹ / ₄ D ³ / ₄ N̄,D ³ / ₄ N̄€D ¹ / ₂ N̄<D ¹ D·D°D ¹ / ₄ D ³ / ₄ D° + oN̄,D ² DμN̄,D ¹ / ₂ N̄<Dμ D _i D»D°D ¹ / ₂ D°D ₃ + D _i N̄€D ³ / ₄ D ² D ³ / ₄ D' + D°D°D±DμD»DμD _i N̄€D ³ / ₄ N̄ D ³ / ₄ D'N̄< + N̄fN̄•N̄,N̄€D ³ / ₄ D ¹ N̄•N̄,D ² D ³ / ₄ N̄fD _i N̄€D°D ² D»DμD ¹ / ₂ D ₃ N̄• + D ¹ / ₄ D°D ³ D ¹ / ₂ D ₃ N̄,		1561.60 €

