

Abloy EL495 FU



Tootekirjeldus

Motor lock EL495-29mm FU push & pull function lock case for narrow profile doors. The Fail Unlocked model for high security two-way AC doors. Exit handle activated in case of a fire alarm.

- Operating voltage: 12-24 V DC, max voltage 700mA (24V), 1700mA (12V)
- Bolt throw: 14mm
- Maximum door weight: 200kg
- Working temperature: -20 to +60 °C
- Backset: 29mm
- Forend: 25mm
- Finish: chrome
- Strike plate: LP702, LP703 (EN1125)
- Cable: EA217, EA227, EA228
- Lead cover: EA281
- Standard EN179 and EN1125

Function:

A pull outside, inside handle or handle and pull: door can be opened by pushing or pulling when the electrical control is on (e.g. timer reader, push button). Inside handle opens the lock always. The door handle works in case of a power failure. The lock has Intelligent Self Diagnostic Function.

Applications:

- Interior and exterior doors of offices, business premises, hospitals and schools
- Exterior doors of apartment buildings
- Exit doors
- Fire rated doors
- Doors with door automatics

TOOTENIMETUS	SOODUS	HIND
ĐæĐ¼Ñ,Đ¼Ñ€Đ½Ñ<Đ¹ Đ·Đ°Đ¼Đ¼Đ° Abloy EL495FU/29 Đ¼Đ¼ (Ñ€ÑƒÑ‡Đ° Đ°Đ°Ñ,Đ,Đ²Đ,Ñ€ÑƒĐµÑ,Ñ•Ñ• Đ¿Ñ€Đ, Đ¼Ñ,Đ°Đ»ÑŽÑ‡ĐµĐ½Đ,Đ, Đ¿Đ,Ñ,Đ°Đ½Đ,Ñ•)		1396.05 €
ĐæĐ¼Ñ,Đ¼Ñ€Đ½Ñ<Đ¹ Đ·Đ°Đ¼Đ¼Đ° Abloy EL495FU/35 Đ¼Đ¼ (Ñ€ÑƒÑ‡Đ° Đ°Đ°Ñ,Đ,Đ²Đ,Ñ€ÑƒĐµÑ,Ñ•Ñ• Đ¿Ñ€Đ, Đ¼Ñ,Đ°Đ»ÑŽÑ‡ĐµĐ½Đ,Đ, Đ¿Đ,Ñ,Đ°Đ½Đ,Ñ•)		1402.82 €

