

ASSA ABLOY DC640



Tootekirjeldus

Rack and pinion door closer with free-swing function

Features

- Supplied with integrated concealed mounting plate, suitable for fire and smoke protection doors
- Door closer DC640 is suitable for fire protection doors
- Electro-hydraulic door closer with magnet hold-open function
- For activating free swing feature, first opening min. 70 degrees
- Can be used for left and right-handed doors
- Can be mounted on door leaf or frame
- Standard and sliding arm with fixed hold-open angle
- Arm system height-adjustable up to 14 mm
- Closing speed, latching speed and backcheck adjustable via front facing regulating valves
- Thermodynamic valves for consistent performance
- Variable adjustable closing force
- Opening angle up to 180°
- Power: 24 V DC
- Dimensions: 400x71x63 mm (length, high, depth)
- Large range of applications

Compatible products:

- Scissor arms: [L690](#), [L190](#), [L199](#), [L198](#)

- Sliding arms: [G694](#), [G195](#)
- Stopper: [A153](#) (if using [G195/G694](#))
- Activator: [2010](#)

TOOTENIMETUS	SOODUS	HIND
D''D²DμÑ€D½Ñ·Dμ D'D³⁄₄D²D³⁄₄D'Ñ‡D, D°D, ASSA ABLOY FD440 EN 3-6 (Ñ€Ñ·Ñ‡D°D¶D½D³⁄₄D¹ Ñ,Ñ·D³D³⁄₄D¹) / EN 3-4 (Ñ,,ÑfD½D°Ñ‡D,Ñ· Ñ·D²D³⁄₄D±D³⁄₄D'D½D³⁄₄D³D³⁄₄ Ñ D³⁄₄D'D°, Ñ·DμÑ€DμD±Ñ€D,Ñ·Ñ,Ñ·D¹)		625.65 €