

Safetron SL630



Tootekirjeldus

- Preload technology
 - Modern piston placement (equivalent to ASSA connect)
 - Adapted for automatic door openers
 - Fire rating: 120 min [E/EI 120]
 - Split function, mechanical inside lever handle
 - Simple function, electric activation both sides
 - Easily adjusted between right or left
 - Certified breaking strength: Grade 3
 - **SL630:** fail secure latch bolt, fail safe handle activation
 - **SL630 SECURE:** fail secure latch bolt, fail secure handle activation
 - emergency exit according to EN 179:2008 with Emergency device 793 & 794
 - Approved with type T emergency opener by Söderhamn innovation
 - Handle movement indication
 - Locked indication
 - Door status indication (with magnet in strike plate)
 - Knob/cylinder indication
 - The product has been assessed by [Byggvarubedomningen](#)
-
- Back set 50 mm
 - Latch bolt length: 14 mm

- Voltage: 12-24 VDC
- Power consumption:

Handle activation:

- 12 VDC: 70mA, 0mA at rest
- 24 VDC: 40mA, 0mA at rest

Duplication of functions:

- 12 VDC: 240mA, 0mA at rest
- 24 VDC: 240mA, 0mA at rest
- Micro switch: Max 30 VDC, 500mA
- Temperature range: -20°C - +40°C

TOOTENIMETUS	SOODUS	HIND
Solenoid lock Safetron SL630		806.08 €
Solenoid lock Safetron SL630 Secure		806.08 €
Solenoid lock Safetron SL630 + cable + lead cover		900.35 €
Solenoid lock Safetron SL630 Secure + cable + lead cover		900.35 €



